


Id. No. 1 with clamping screw DIN 912, zinc plated

Id. No. 2 with Stainless Steel-clamping screw DIN 912

d ₁	k	d ₂	d ₃	l ₁	l ₂	t	x ₁	x ₂	y ₁	y ₂	Clamping lever for d ₃
Bore B	Clamping length		Clamping screw								
B 20	50	6,5	M 8	52	40	7	60	42	60	42	GN 911-M 8-32
B 25	50	6,5	M 8	52	40	7	60	42	60	42	GN 911-M 8-32
B 30	50	6,5	M 8	52	40	7	60	42	60	42	GN 911-M 8-32
B 30	70	8,5	M 10	68	56	10	90	64	90	64	GN 911-M10-40
B 32	70	8,5	M 10	68	56	10	90	64	90	64	GN 911-M10-40
B 35	70	8,5	M 10	68	56	10	90	64	90	64	GN 911-M10-40
B 40	70	8,5	M 10	68	56	10	90	64	90	64	GN 911-M10-40
B 40	85	11	M 10	77,5	65	14	105	74	105	74	GN 911-M10-55
B 42	85	11	M 10	77,5	65	14	105	74	105	74	GN 911-M10-55
B 45	85	11	M 10	77,5	65	14	105	74	105	74	GN 911-M10-55
B 48	85	11	M 10	77,5	65	14	105	74	105	74	GN 911-M10-55
B 50	85	11	M 10	77,5	65	14	105	74	105	74	GN 911-M10-55
B 55	100	11	M 10	92	80	14	125	89	125	89	GN 911-M10-55
B 60	100	11	M 10	92	80	14	125	89	125	89	GN 911-M10-55

Specification

- ▶ Aluminium plastic coated black **SW** RAL 9005 textured finish
- blank **BL** matt shot-blasted
- ▶ Clamping bores machined
- ▶ Socket cap screws DIN 912 Steel zinc plated / St. Steel German material No. 1.4301
- ▶ Hexagon nuts DIN 985 Steel zinc plated / St. Steel German material No. 1.4301
- ▶ Adjustable clamping lever GN 911 Inserts / Distance bushings Stainless Steel German Material No. 1.4305

Information

The clamping bores of the base plate connector clamps GN 163 (photo page 22) are machined and designed for construction tubings GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard clamping bolt is a socket cap screw DIN 912. It can be replaced by an adjustable clamping lever GN 911 (see table of dimensions).

Construction tubings GN 990 page 59

Base plate linear actuator connectors GN 163.1 page 77

How to order

Base plate connector clamp GN 163-B40-85-1-BL

Code No.				
	d ₁	k	Id. No.	Finish

Adjustable clamping levers GN 911 have to be ordered separately. They are supplied disassembled.