



Adjustable clamping lever GN 911



Id. No. 1 with 2 clamping screws DIN 912, zinc plated Id. No. 2 with 2 Stainless Steel-clamping screws DIN 912

d ₁		d ₂		d ₃	k	l ₁	l ₂	m	Clamping lever for d ₃
Bore B	Material	Bore B	Material	Clamping screw	Clamping length				Distance bushing
B 10	Aluminium	B 10	Aluminium	M 6	25	61	34,5	39	GN 911-M6-22
B 12	St. Steel	B 12	St. Steel	M 6	25	61	34,5	39	GN 911-M6-22
B 14	St. Steel	B 14	St. Steel	M 6	25	61	34,5	39	GN 911-M6-22
B 15	Aluminium	B 15	Aluminium	M 6	25	61	34,5	39	GN 911-M6-22
B 16	St. Steel	B 16	St. Steel	M 6	25	61	34,5	39	GN 911-M6-22
B 18	St. Steel	B 18	St. Steel	M 6	25	61	34,5	39	GN 911-M6-22

Specification

- ▶ Aluminium plastic coated black **SW** RAL 9005 textured finish
- ▶ blank **BL** matt shot-blasted
- ▶ Stainless Steel **NI** German Material No. 1.4308 matt polished
- ▶ Clamping bores machined
- ▶ Socket cap screws DIN 912 Steel zinc plated / St. Steel German material No. 1.4301
- ▶ Hexagon nuts DIN 985 Steel zinc plated / St. Steel German material No. 1.4301
- ▶ Adjustable clamping lever GN 911 Zinc die casting Inserts / Distance bushings Stainless Steel German Material No. 1.4305

Information

The clamping bores of the T-angle connector clamps GN 191 (photo page 29) are machined and designed for construction tubings GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard clamping bolts are socket cap screws DIN 912. They can be used in place of adjustable clamping levers GN 911 (see table of dimensions).

Special executions:
different combinations of bores d₁ / d₂

Construction tubings GN 990 page 59

T-angle linear actuator connectors GN 191.1 page 78

How to order

T-angle connector clamp GN 191-B12-B12-1-SW

Code No.				
	d ₁	d ₂	Id. No.	Finish

Stainless Steel-T-angle connector clamp GN 191-B16-B16-2-NI

Code No.				
	d ₁	d ₂	Id. No.	Material

Adjustable clamping levers GN 911 have to be ordered separately. They are supplied disassembled.