


Id. No. 1 with 4 clamping screws DIN 912, zinc plated    Id. No. 2 with 4 Stainless Steel-clamping screws DIN 912

d <sub>1</sub>	s <sub>1</sub>	d <sub>2</sub>	s <sub>2</sub>	k	d <sub>3</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	m	Clamping lever for d <sub>3</sub>
Bore B	Square V	Bore B	Square V	Clamping length	Clamping screw					 Distance bushing
B 20	V 20	B 20	V 20	50	M 8	120	68	46	85	GN 911-M 8-40
B 25	V 25	B 25	V 25	50	M 8	120	68	46	85	GN 911-M 8-40
B 30	V 30	B 30	V 30	50	M 8	120	68	46	85	GN 911-M 8-40
B 30	V 30	B 30	V 30	60	M 8	141	79	59	101,5	GN 911-M 8-55
B 32	-	B 32	-	60	M 8	141	79	59	101,5	GN 911-M 8-55
B 35	V 35	B 35	V 35	60	M 8	141	79	59	101,5	GN 911-M 8-55
B 40	V 40	B 40	V 40	60	M 8	141	79	59	101,5	GN 911-M 8-55
B 40	V 40	B 40	V 40	76	M 10	176	98	70	126	GN 911-M10-63
B 42	-	B 42	-	76	M 10	176	98	70	126	GN 911-M10-63
B 45	V 45	B 45	V 45	76	M 10	176	98	70	126	GN 911-M10-63
B 48	-	B 48	-	76	M 10	176	98	70	126	GN 911-M10-63
B 50	V 50	B 50	V 50	76	M 10	176	98	70	126	GN 911-M10-63

### Specification

- ▶ Aluminium plastic coated black **SW** RAL 9005 textured finish
- blank **BL** matt shot-blasted
- ▶ Clamping bores not machined
- ▶ Socket cap screws DIN 912 Steel zinc plated / St. Steel German material No. 1.4301
- ▶ Hexagon nuts DIN 985 Steel zinc plated / St. Steel German material No. 1.4301
- ▶ Adjustable clamping lever GN 911 Zinc die casting Inserts / Distance bushings Stainless Steel German Material No. 1.4305 page 63

### Information

The clamping bores of the T-angle connector clamps GN 194 (photo page 29) are not machined and designed for construction tubings GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

Within the same nominal size the T-angle connector clamp bores can be supplied with the bores d<sub>1</sub> and d<sub>2</sub> and square bores s<sub>1</sub> and s<sub>2</sub> i.e. in combination with d<sub>1</sub> and s<sub>2</sub> or s<sub>1</sub> and d<sub>2</sub>.

The standard clamping bolts are socket cap screws DIN 912. They can be replaced by adjustable clamping levers GN 911 (see table of dimensions).

Construction tubings GN 990 page 59

### How to order

**T-angle connector clamp**  
GN 194 - B42 - B42 - 76 - 1 - BL

Code No.					
d <sub>1</sub> (s <sub>1</sub> )		d <sub>2</sub> (s <sub>2</sub> )		k	
Id. No.		Finish			

**T-angle connector clamp**  
GN 194 - V50 - B50 - 76 - 2 - SW

Code No.					
s <sub>1</sub> (d <sub>1</sub> )		d <sub>2</sub> (s <sub>2</sub> )		k	
Id. No.		Finish			

Adjustable clamping levers GN 911 have to be ordered separately. They are supplied disassembled.