



Type **A** with male thread

Type **B** with female thread

d ₁		d ₂	d ₃	e	k ₁	k ₂	k ₃	l ₁ ≈	l ₂	l ₃ min.	l ₄	A / F	x max. shaft off-set	max. pull- push load [kN]
M 6	-	42	5,5	11	7	14	28	30,5	11	11	14	10	0,6	2,5
M 8	-	48	6,5	14,5	8	16	32	35,5	13	13,5	17	13	0,7	4,5
M 10	M 10 × 1,25	50	6,5	19	9	17	34	43	16	16	20	17	0,7	6,5
M 12	M 12 × 1,25	55	6,5	21	10	19	38	53	20,5	21	25	19	0,8	10
M 16	M 16 × 1,5	65	9	27	12,5	22,5	45	64	23	25	30	24	1	18
M 20	M 20 × 1,5	80	11	34	17	28	56	74	26	29	35	30	1	30

Specification

Steel
tempered
phosphated

Information

Quick-fit couplings GN 240.1 (photo page 791) have been designed for the purpose of compensating a radial shaft off-set (x).

A typical application is the axial link to a piston rod of a cylinder operating in any type of fixture or system.

The coupling is **not** designed for the transfer of torque.

Quick-fit couplings GN 240
(with radial off-set compensation)

Page 790

How to order

**Quick-fit coupling
GN 240.1-M12x1,25-B**

Code No.			
	d ₁		Type