


Id. No. 1 with 3 clamping screws DIN 912, zinc plated

Id. No. 2 with 3 Stainless Steel-clamping screws DIN 912

d <sub>1</sub>	d <sub>2</sub>	b	d <sub>3</sub>	k <sub>1</sub>	k <sub>2</sub>	l <sub>1</sub>	l <sub>2</sub>	m <sub>1</sub>	m <sub>2</sub>	Clamping lever for d <sub>3</sub>
Bore B	Bore B	Swivel width	Clamping screw							
B 12	B 12	25	M 6	25	25	100	34,5	29,5	48,5	GN 911-M6-22
B 14	B 14	25	M 6	25	25	100	34,5	29,5	48,5	GN 911-M6-22
B 16	B 16	25	M 6	25	25	100	34,5	29,5	48,5	GN 911-M6-22
B 18	B 18	25	M 6	25	25	100	34,5	29,5	48,5	GN 911-M6-22

### Specification

- ▶ Aluminium plastic coated black **SW** RAL 9005 textured finish
- blank **BL** matt shot-blasted
- ▶ Clamping bores machined
- ▶ Socket cap screws DIN 912 Steel zinc plated / St. Steel German material No. 1.4301
- ▶ Hexagon nuts DIN 985 Steel zinc plated / St. Steel German material No. 1.4301
- ▶ Adjustable clamping lever GN 911 Zinc die casting Inserts / Distance bushings Stainless Steel German Material No. 1.4305 page 63

### Information

The swivel clamp connector joints GN 283 (photo page 46 / 47) are an assembly of the swivel clamp connectors GN 273 and GN 275. Since the swivel clamp connectors have an identical swivel width "b", all bores "d<sub>1</sub> / d<sub>2</sub>" can be combined as required.

The clamping bore is machined and designed for construction tubings GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard clamping bolts are socket cap screws DIN 912. They can be replaced by adjustable clamping levers GN 911 (see table of dimensions).

*Construction tubings GN 990* page 59

*Swivel clamp connectors GN 273* page 40

*Swivel clamp connectors GN 275* page 42

### How to order

**Swivel clamp connector joint GN 283-B12-B14-1-SW**

Code No.				
	d <sub>1</sub>	d <sub>2</sub>	Id. No.	Finish

Adjustable clamping levers GN 911 have to be ordered separately. They are supplied disassembled.