



d ₁	d ₂	l ₁			d ₃	l ₂	l ₃	l ₄ Adjustable range	l ₅	l ₆	l ₇	A/F ₁	A/F ₂	Static load [kN] (see information)	
60	M 16	125	150	175	200	24	45	13	32	4	16	45	20	12	27
80	M 16	128	153	178	203	24	45	13	32	5	18	45	20	12	24
80	M 20	152	177	202	252	30	56	16	40	5	18	56	24	16	24
80	M 24	176	226	276		35	67	19	48	5	18	67	30	20	24
100	M 16	130	155	180	205	24	45	13	32	6	20	45	20	12	21
100	M 20	155	180	205	255	30	56	16	40	6	20	56	24	16	21
100	M 24	179	229	279		35	67	19	48	6	20	67	30	20	21

Specification

Stainless Steel Foot

German Material No. 1.4301 matt shot blasted

Bolt, adjustable sleeve German Material No. 1.4305

Rubber underlay (Perbunan NBR) 85 ÷ 90 Shore hardness bonded, black

Assembly screw Stainless Steel, lockited

Stainless Steel characteristics Page 894

Elastomere (rubber) characteristics Page 896

Information

Stainless Steel-Levelling feet for application in hygiene environment GN 341.1 (photo page 701) have been designed to meet requirements in the food industry:

With the convex shaped bolt head seat on the Stainless Steel-foot, the formation of deposits is greatly reduced and the cleaning is simplified.

The rubber underlay is firmly bonded into the Stainless Steel-foot. The adjustable sleeve is shrouding the thread over its adjustable length and sharp edges and corners have been to a large extent avoided.

Levelling feet GN 341.1 get the EQUIPMENT ACCEPTANCE CERTIFICATE of the USDA (US-Department of Agriculture).

The load figures specified in the table above are based on a series of tests whereby a vertical load in relation to the horizontal plane of the foot is applied. If the above figures are exceeded, a permanent deformation of the Stainless Steel-foot can occur.

How to order

Stainless Steel-Levelling foot GN 341.1-100-M20-180

Code No.	d ₁	d ₂	l ₁