

Identification no. 1 without vent drilling

• Identification no. 2 without vent drilling

d1	d2	d3 Vent drilling	d4	l1 ±0,5	l2	l3	s	t min.
22	G ¾ M 16 x 1,5	2	M 5	26	8	15	5	8
26	G ½ M 20 x 1,5	2	M 5	27,5	8,5	16	5	8
32	G ¾ M 26 x 1,5	2	M 5	29	9	17	6	8
40	G 1 -	2	M 5	32,5	11	18	7	8

Specification

- ▶ Aluminium plastic coated black **SW** RAL 9005 textured finish

blank **BL**
tumbled

- ▶ **GN 441**
temperature resistant up to 100° C
Sealing ring rubber
NBR (Perbunan)
- ▶ **GN 442**
temperature resistant up to 200° C
Sealing ring rubber
FPM (VITON®)

Information

Threaded plugs GN 441 / GN 442 with the external diameter d1 match the screw-in holes for DIN 3852 pipe bolt connections.


The sealing ring is embedded in a radial recess on the plane side, which makes the sealing ring captive and cannot be squeezed out during tightening. The sealing is also relatively soft, enhancing the sealing effect also on uneven surfaces.

Threaded plugs with dipstick on request.


*Threaded plugs GN 741 / GN 742
general catalogue page 752*

How to order

**Threaded plug
GN 441-22-M16x1,5-1-BL**



**Threaded plug
GN 442-40-G1-1-SW**



The types marked thus • are as usually not in stock.