


Type A with bore

Type W with bolt

d ₁ Bore B for shaft tol. h11	d ₂ H9 Type A	d ₃ Type W	k	d ₄ Clamping thread	d ₅	l ₁	l ₂	l ₃	l ₄	t	s Square V	Clamping lever for d ₄  Distance bushing
B 8	B 8	8	16	M 4	M 4	16	13	26	5,5	8	-	GN 511-M4-16
B 10	B 10	10	20	M 5	M 5	17	15,5	31,5	7	10	8	GN 511-M5-20
B 12	B 12	12	20	M 5	M 5	19	16,5	35,5	8	12	10	GN 511-M5-20
B 15	B 15	15	25	M 6	M 6	21	20	43,5	10	15	12	GN 511-M6-25
B 16	B 16	16	25	M 6	M 6	24	20	45	11	16	-	GN 511-M6-25

Specification

- ▶ Aluminium
matt **MT**
ground
anodized **ELS**
black
- ▶ Bolt (Type W)
Steel
zinc plated, blue passivated
- ▶ Socket cap screws DIN 912
Stainless Steel
German Material No. 1.4301
- ▶ Adjustable
clamping lever GN 511
Inserts / Distance bushings
Stainless Steel
German Material No. 1.4305

page 14

Information

The standard clamping bolts are socket cap screws DIN 912. They can be used in place of adjustable clamping levers GN 511 (see table of dimensions).

Retaining rods / tubings GN 480.1 page 13

How to order

T-Clamp mounting GN 476-B12-B12-A-MT

Code No.				
	d ₁	d ₂	Type	Finish

T-Clamp mounting with bolt GN 476-B12-12-W-ELS

Code No.				
	d ₁	d ₃	Type	Finish

Adjustable clamping levers GN 511 have to be ordered separately. They are supplied disassembled.