



d ₁	Tolerances		Material of the magnet HF					Material of the magnet SC / ND					Nominal adhesive forces [N]		
	HF	SC ND	d ₂	d ₃	h	l	t	d ₂	d ₃	h	l	t	HF	SC	ND
6	-	±0,1	-	-	-	-	-	M 3	6 ±0,1	4,5 ±0,1	7	6	-	5	5
8	-	±0,1	-	-	-	-	-	M 3	6 ±0,1	4,5 ±0,1	7	6	-	11	13
10	±0,1	±0,1	M 3	6 ±0,1	4,5 +0,2/-0,1	7	5	M 3	6 ±0,1	4,5 ±0,1	7	6	4	20	25
13	±0,1	±0,1	M 3	6 ±0,1	4,5 +0,2/-0,1	7	5	M 3	6 ±0,1	4,5 ±0,1	7	6	10	40	60
16	±0,1	±0,1	M 3	6 ±0,1	4,5 +0,2/-0,1	7	5	M 4	6 ±0,1	4,5 ±0,1	7	6	18	60	95
20	±0,1	±0,1	M 3	6 ±0,1	6 +0,2/-0,1	7	5	M 4	8 ±0,2	6 ±0,1	7	7	30	90	140
25	±0,1	±0,1	M 4	8 ±0,1	7 +0,3/-0,1	8	7	M 4	8 ±0,2	7 ±0,2	7	7	40	150	200
32	±0,1	±0,1	M 4	8 ±0,1	7 +0,3/-0,1	8	7	M 5	10 ±0,2	7 ±0,2	8,5	8	80	220	350
40	+0,2/-0,1	-	M 5	10 ±0,1	8 +0,4/-0,1	10	9	-	-	-	-	-	125	-	-
50	+0,2/-0,1	-	M 6	12 ±0,1	10 +0,5/-0,1	12	11	-	-	-	-	-	220	-	-
63	+0,3/-0,1	-	M 8	15 ±0,1	14 +0,5/-0,1	16	14	-	-	-	-	-	350	-	-
80	+0,5/-0,1	-	M 10	20 ±0,1	18 +0,5/-0,1	16	15	-	-	-	-	-	600	-	-
100	+0,5/-0,1	-	M 12	22 ±0,1	22 +0,5/-0,1	21	18	-	-	-	-	-	900	-	-
125	+0,5/-0,1	-	M 14	25 ±0,1	26 +0,5/-0,1	24	20	-	-	-	-	-	1300	-	-

Specification

- ▶ Housing / threaded bush
Steel, zinc plated

Materials of the magnet:

- ▶ **Hard ferrite HF**
temperature resistant up to 200° C
- ▶ **SmCo SC**
Samarium, cobalt
temperature resistant up to 200° C
- ▶ **NdFeB ND**
Neodymium, iron, boron
temperature resistant up to 80° C

Information

Retaining magnets GN 50.2 are a shielded magnetic system.

Further details for retaining magnets

page 3 et seq.

How to order

**Retaining magnet
GN 50.2-HF-20-M3**

Code No.			
Material			
d ₁			
d ₂			