



Plunger retracted  
(if  $l_1 = d_1$ )

**Range extended!**

**INOX**  
STAINLESS  
STEEL

d <sub>1</sub> Plunger $^{-0,02}$ $^{-0,04}$ Bore H7	l <sub>1</sub>	b <sub>1</sub>	b <sub>2</sub>	d <sub>2</sub> $^{-0,02}$ $^{-0,1}$	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	k	l <sub>2</sub>	l <sub>3</sub> $^{-0,15}$	l <sub>4</sub>	l <sub>5</sub> Stroke	Spring load N <sub>≈</sub>		Axial load [N]	
													initial	end		
6	6	14	40	18	10	25	4,3	8,3	30	37 / 45	2,5	4,5	6	8,5	22	400
8	8	18	46	20	12	31	5,3	10,4	34	44 / 54	2,5	5,5	8	15,5	28	500

### Specification

- ▶ Body  
Zinc die casting  
zinc plated, blue passivated
- ▶ Knob  
Plastic (Polyamide PA)  
black matt finish  
not removable
- ▶ **GN 608**  
Plunger Steel  
hardened  
Single components  
Steel / brass

- NEW ▶ GN 608.5**  
Plunger Stainless Steel  
German Material No. 1.4305  
chemically nickel plated  
Single components  
Stainless Steel

### Information

A special feature of Indexing plungers GN 608 / GN 608.5 is their reduced dimension. This concept has been introduced for mounting on thin walled parts by means of countersunk screws or rivets.

*Indexing plungers GN 607*  
general catalogue page 408

### How to order

#### Indexing plunger GN 608-8-18

Code no. | | |  

#### Stainless Steel- Indexing plunger GN 608.5-6-14

Code no. | | |  