



Type **A** without protective cap

Type **B** with protective cap

d ₁	Length l ₁			d ₂	h ₁	h ₂	l ₂	m	A/F
M 4	23			11	3	6,5	2,5	3,2	7
M 5	38			12	3,5	8	2,5	4,7	8
M 6	29	49		15	4	10	4	5,2	10
M 8	36	56	96	19	5,5	13	5,5	6,8	13
M 10	43	77	127	24	6,5	16	7	8,4	16
M 12	53	88	128	26	7,5	19	8,5	10,8	18
M 14 ¹⁾	54			—	9	—	—	12,8	21

Specification

Hexagon bolt
 ISO 4017 / DIN 933
 steel
 tensile strength 800 N/mm²
 zinc plated, blue passivated

Stainless Steel **NI**
 German Material No. 1.4301
 only size M 4 ÷ M 8

Hexagon nuts ISO 4032
 steel
 zinc plated, blue passivated

Stainless Steel
 German Material No. 1.4301

Protective caps
 GN 806 Page 491

Stainless Steel
 characteristics Page 894

¹⁾ Clamping bolt M 14 is not available as type B with protective cap.

Information

The elastic protective caps GN 806 can easily be fitted to the bolt head.

How to order

Clamping bolt GN 807-M8-56-B

Code No.			
	d ₁	Length l ₁	Type

Stainless Steel- Clamping bolt GN 807-M6-29-A-NI

Code No.				
	d ₁	Length l ₁	Type	Stainless Steel

The two hexagon nuts are included parts of the order.