



d ₁	d ₂	l ₁				l ₂	l ₃ ≈	m	A/F
15	M 6	26	36	46		7,6	3,6	5,2	3
15	M 8	20	35	45	58	7,6	2,5	6,8	4
18	M 8	20	35	45	58	9,2	4,2	6,8	4
18	M 10	34	44	57	74	9,2	3,4	8,4	5
21	M 8	20	35	45	58	10	5	6,8	4
21	M 10	34	44	57	74	10	4,3	8,4	5
21	M 12	34	57	74	94	10	3,4	10,8	6
25	M 8	20	35	45	58	10,5	5,5	6,8	4
25	M 10	34	44	57	74	10,5	4,6	8,4	5
25	M 12	34	57	74	94	10,5	3,6	10,8	6
32	M 8	20	35	45	58	11	6	6,8	4
32	M 10	34	44	57	74	11	5	8,4	5
32	M 12	34	57	74	94	11	4,2	10,8	6
40	M 8	20	35	45	58	13	8	6,8	4
40	M 10	34	44	57	74	13	7	8,4	5
40	M 12	34	57	74	94	13	6,2	10,8	6

2.4

Specification

Clamping pad
Plastic
Technopolymer
(Polyacetal POM)
temperature resistant up to 80° C
black, matt

Grub screw
Steel **ST**
Tensile strength 500 N/mm²
blackened

Stainless Steel **NI**
German Material No. 1.4305

Hexagon nuts ISO 4032
steel
zinc plated, blue passivated

Stainless Steel
German Material No. 1.4305

Information

The ball end of the grub screw can be hit easily into the clamping pad and removed.

Levelling feet
GN 343.1 ÷ GN 343.8

Page 682 ÷ 687

How to order

Clamping bolt
GN 903-21-M12-57-NI

Code No.	d ₁	d ₂	l ₁	Material

Clamping bolts GN 903 are supplied unassembled.

The two hexagon nuts are included parts of the order.