

Standard	Characteristics / Features	Materials						Opening angle		Mounting by		Welding		
		ST	NI	A4	ZD	AL	KT	positive	negative	Screw fastening from the front	Screw fastening from the rear			
GN 237 Page 959 				x	x	x	x			180°	90°	x	x	
GN 237 Page 963 				x						180°	90°	x	x	
GN 237.1 Page 964 												x		
GN 136 Page 965 				x	x					180°	90°	x		x
GN 138 Page 966 														x
GN 151 Page 965 												x	x	
GN 159 Page 968 												x		
GN 159.1 Page 970 												x		
GN 161 Page 972 												x		
GN 129 Page 974 			x									∞	∞	x

Standard	Characteristics / Features	Materials						Opening angle		Mounting by		Welding	
		ST	NI	A4	ZD	AL	KT	positive	negative	Screw fastening from the front	Screw fastening from the rear		
GN 129.5 Page 975  Iron Stainless Steel		Corner mounted, three parts		x	x				∞	∞		x	
GN 129.2 Page 976  Iron Stainless Steel		extended three parts	x	x	x				180°	90°		x	
GN 129.3 Page 977		extended three parts	x						180°	90°	x		
GN 238 Page 978		adjustable, 2-dimensional				x			160°	20°	x		
GN 127 Page 980		adjustable, 1- or 2-dimensional				x			170°	90°	x		
GN 151.4 Page 981		adjustable, 1- or 2-dimensional					x		180°	30°	x		
GN 437 Page 982		with adjustable friction				x			180°	90°	x		
GN 233 Page 984		with adjustable friction					x		180°	90°	x		
GN 337 Page 986  Iron Stainless Steel		detachable, Accessory available		x		x			180°	90°	x		
GN 161.1 Page 988		detachable, corner mounted				x		x	∞	∞	x	x	

3.1

3.2

3.3

3.4

3.5








3.6

3.7

3.8

3.9



Standard	Characteristics / Features	Materials						Opening angle		Mounting by		Welding
		ST	NI	A4	ZD	AL	KT	positive	negative	Screw fastening from the front	the rear	
GN 161.2 Page 989 	detachable				x			180°	0°		x	
GN 128 Page 990 	Corner mounted, detachable	x						∞	∞			x
GN 128.2 Page 991 	Corner mounted, detachable		x	x		x		∞	∞			x
GN 139.1 Page 992 	with electrical safety switch function				x			180°	0°		x	
GN 139.5 Page 966 	with electrical safety switch function			x				180°	0°		x	
GN 239.6 Page 998 	with electrical safety switch function						x	180°	0°	x	x	
GN 239.7 Page 998 	versatile						x	180°	0°	x	x	
GN 239.4 Page 1002 	with electrical switch function						x	180°	10°	x		
GN 239.3 Page 1002 	versatile						x	180°	10°	x		